

# ReSound Up Smart™

Because every word matters

ReSound Up Smart™ is a premium hearing aid family for children of all ages and hearing losses. It is a game changer in the way children are granted easy and direct access to the sounds they need for speech and language development. ReSound Up Smart meets or surpasses all pediatric requirements, including safety requirements.

Surround Sound by ReSound™ ensures audibility and consistently clear and comfortable sound, even at high output levels, in all listening situations, due to advanced pediatric features.

As the first pediatric Made for iPhone hearing solution, ReSound Up Smart 9, 7 and 5 receives stereo sound directly from an iPhone, iPad or iPod touch to benefit listening and language learning in more fun ways for infants and pre-schoolers, and to provide educational and social media interaction possibilities for older children and teens. And with the ReSound Smart™ app, the child or the parent can adjust the hearing aids easily, discreetly and intuitively from iOS devices.

ReSound Up Smart offers a line-up of modern and powerful wireless BTEs for mild to profound hearing losses with attractive colour options.

## Product features

- Wireless connectivity to ReSound Unite accessories
- Wireless ear-to-ear connectivity
- Full iSolate™ nanotech coating
- Supports open and closed configurations
- Push button and programmable Volume Control
- Size 13 battery
- Battery door with integrated On/Off switch
- Advanced, auto-locking battery door
- LED visual indication
- Telecoil with T and MT modes

## Options

- 12 different colour combinations
- Direct audio input or integrated FM
- Supports Dome, Tulip-Dome and Standard Earmold
- Standard hook, Child hook, Baby hook and Thin Tube adaptor

## Fitting software

- Aventa fitting software (3.10 or higher)
- Wireless fitting interface: Airlink™
- Programming adaptor with CS44 socket cable
- Speedlink, HI-Pro, or NOAHlink programming interfaces

UPS977-DLW  
UPS777-DLW  
UPS577-DLW  
UPS577M-DLW




ReSound Up Smart 9  
ReSound Up Smart 7  
ReSound Up Smart 5

	ReSound Up Smart 9	ReSound Up Smart 7	ReSound Up Smart 5
ReSound SmartRange chip	●	●	●
<b>Surround Sound by ReSound</b>			
Model			
WARP™ Compression - number of bands	17	17	9
Environmental Classifier	●	●	●
Sound Shaper™	●	●	●
<b>Clean</b>			
NoiseTracker™ II	●	○	○
Personalized Noise Reduction	●		
WindGuard™	●	○	○
Expansion	●	○	○
<b>Balance</b>			
Binaural Directionality™	●		
Directional Mix Processor	●	●	●
- Adjustable directional mix	●		
Natural Directionality™ II	●	●	
Synchronized SoftSwitching™	●	●	
SoftSwitching™			●
AutoScope Adaptive Directionality™	●		
MutiScope Adaptive Directionality™	●	●	
Adaptive Directionality			●
Binaural Environmental Optimizer™ II	●		
Environmental Optimizer™ II	●		
Environmental Optimizer™		●	
<b>Stabilize</b>			
DFS Ultra™ II	●	●	●
- Music Mode™	●	●	●
Auto DFS™	●	●	●
<b>Convenience Features</b>			
Synchronized Push Button	●	●	●
Synchronized Volume Control	●	●	●
SmartStart™	●	●	●
PhoneNow™	●	●	●
Comfort Phone™	●	●	●
iSolate™ nanotech	●	●	●
<b>Fitting Features</b>			
Gain Handles	9	9	9
Fully Flexible Programs	4	4	4
Synchronized Acceptance Manager	●	●	●
Onboard Analyzer™ II	●	●	●
In Situ Audiometry	●	●	●
<b>Wireless connectivity</b>			
2.4 GHz Wireless Technology	●	●	●
2.4 GHz ear-to-ear communication	●	●	●
Direct audio streaming (Made for iPhone)*	●	●	●
Wireless fitting with Airlink™	●	●	●
ReSound Unite™ TV Streamer 2	●	●	●
ReSound Unite™ Remote Control 2	●	●	●
ReSound Unite™ Phone Clip+	●	●	●
ReSound Unite™ Mini Microphone	●	●	●
ReSound Control™ app (Phone Clip+ required)	●	●	●
ReSound Smart™ app*	●	●	●

\*Available in UPS577M-DLW

## Fitting range



ReSound Up Smart is compatible with iPhone 6s Plus, iPhone 6s, iPhone 6 Plus, iPhone 6, iPhone 5s, iPhone 5c, iPhone 5, iPad Pro, iPad Air 2, iPad Air, iPad (4th generation), iPad mini 4, iPad mini 3, iPad mini 2, iPad mini and iPod touch (5th generation) using iOS 7.X or later. Apple, the Apple logo, iPhone, iPad, iPad Air, iPad mini and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries.

# ReSound

rediscover hearing

○ Standard  
● Advanced  
● Ultimate


# ReSound Up Smart™

## Technical specifications


		UPS77-DLW Open UPS77M-DLW Open		UPS77-DLW Closed UPS77M-DLW Closed		
		IEC 60118-0 IEC 711 Ear simulator	IEC 60118-7 ANSI S3.22 2cc coupler	IEC 60118-0 IEC 711 Ear simulator	IEC 60118-7 ANSI S3.22 2cc coupler	
Reference test gain (60 dB SPL input)	1600 Hz/HFA	44	41	47	47	dB
Full-on gain (50 dB SPL input)	Max.	62	51	66	59	dB
	1600 Hz/HFA	53	46	56	52	
Maximum output (90 dB SPL input)	Max.	130	122	134	128	dB SPL
	1600 Hz/HFA	126	118	130	123	
Total harmonic distortion	500Hz	0.2	0.1	0.5	0.4	%
	800 Hz	0.5	0.2	0.6	0.4	
	1600 Hz	0.4	0.5	0.6	0.5	
Telecoil sensitivity (1 mA/m input)	Max.	91	-	94	-	dB SPL
Full-on Telecoil sensitivity @ 1mA/m	1600 Hz / HFA	81	75	84	81	
HFA – SPLIV @ 31.6 mA/m (ANSI)	HFA	-	99	-	106	
Equivalent input noise w/o Noise reduction		23	23	23	22	dB SPL
1/3 Octave Equivalent input noise, w/o Noise reduction		10		10		
Frequency range (DIN 45605/ANSI)		100-6900	100-6770	100-7080	100-6850	Hz
Current drain		1.1	1.2	1.1	1.2	mA

Data in accordance with IEC 60118-0, IEC 60118-7; Supply Voltage 1.3 V.


Maximum Output (OSPL 90)




Maximum Output (OSPL 90)




Full-On and Reference Test Gain




Full-On and Reference Test Gain



Telecoil response  
Input level 10 mA/m



Input/Output Response



Measured according to IEC 60 118-0 1983, amendment 1994; at 1.3 V, impedance 6.2 ohms and 23°C on O.E.S. according to IEC711 1981, resp on 2cc according to IEC60118-7 2nd edition 2005 (DIN average calculated at 500 Hz, 1000 Hz and 2000 Hz; HFA average calculated at 1000 Hz, 1600 Hz and 2500 Hz; 0 dB SPL sound pressure equals 20µPa). All measurements without DSP features activated unless indicated otherwise.

■ Open  
■ Closed

**Basic settings:**

Full-on Gain, Reference Test Gain  
MPO = Maximum Peak Output  
Maximum Band Width

Patents pending

All specifications are subject to change without notice

400310000-GB-15.09-Rev.D

**ReSound A/S**  
Lautrupbjerg 7  
DK-2750 Ballerup, Denmark  
Tel.: +45 45 75 11 11  
Fax: +45 45 75 11 19  
www.resound.com

**United Kingdom**  
GN ReSound Ltd.  
Kirtlington Business Centre  
Portway  
Kirtlington  
Oxon OX5 3JA  
Tel.: +44 1869 352 800  
Fax: +44 1869 343 466  
www.gnresound.co.uk

**Australia**  
GN ReSound Pty. Ltd.  
Gate C, 19-25 Khartoum Rd  
Macquarie Technology Park  
Macquarie Park NSW 2113  
Tel.: (free) 1800 658 955  
www.gnresound.com.au

**New Zealand**  
GN ReSound (NZ) Ltd.  
Ground Floor, North Entrance  
4 Fred Thomas Drive  
Takapuna  
Auckland, 0622  
Tel.: (free) 0800 900 126  
Fax: (free) 0800 007 695  
www.gnresound.co.nz